

**Product data sheet**

**HDY3654440**

**Characteristics**

**Surge Protective Device HDY3 -65 - 4P - 440V**



**Main**

Range of product	HDY3
Product or component type	Surge protection device
Body type	Plug-in

**Complementary**

Poles description	4P
Nominal discharge current	30.0 kA
Maximum discharge current	65.0 kA
[Uc] maximum continuous operating voltage	440.0 V
Maximum [Up] voltage protection level	3.5 kV
Remote signalling	Without
[Ue] rated operational voltage	125 V
Local signalling	Indicator light (green) for operating Indicator light (red) for fault
Mounting support	35 mm DIN rail
Location of connection	Top
Cable cross section	4...16 mm <sup>2</sup> flexible cable 4...25 mm <sup>2</sup> rigid cable
Response time	= 25 ns
Height	100 mm
Width	72 mm
Depth	70 mm

**Environment**

Electromagnetic compatibility	8/20 µs wave immunity
Operating altitude	= 2000 m
Standards	IEC 61643-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.