



**Product data sheet**

**HLAY5BL8325**

**Characteristics**

**Double-headed push-button, HLAY5, 1 NO + 1 NC, 2 flush push-buttons**



**Main**

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Double-headed push-button
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard

**Complementary**

Cap/operator or lens colour	Green + red
Fixing collar material	Metal
Shape of signaling unit head	Rectangular
Type of operator	Spring return
Operator profile	Green flush, I Red flush, O
Operator profile	2 flush push-buttons
Contacts type and composition	1 NO + 1 NC
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles
E-commerce address	Hlay5-pushbuttons-mushroom-and-emergency-stop-pushbuttons-1

**Environment**

Ambient air temperature for operation	-5...40 °C
IP degree of protection	IP40 IP65 with protective cover
Standards	IEC 60947-5-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.